

SECTION 09651 - RESILIENT TILE FLOORING

A. SUMMARY

1. [Solid vinyl] [Rubber] [Vinyl composition] floor tile.
2. Resilient wall base and accessories.
3. Substrate: [Concrete] [Wood].

B. MATERIALS

1. Solid Vinyl Floor Tile:
 - a. Class: [I, monolithic] [II, surface decorated] [III, printed film].
 - b. Type: [Smooth] [Embossed] surface.
 - c. Thickness: [0.080 inch (2.0 mm)] [0.100 inch (2.5 mm)] [0.120 inch (3.0 mm)] [1/8 inch (3.2 mm)].
 - d. Size: [12 by 12 inches (305 by 305 mm)] [18 by 18 inches (457 by 457 mm)] [24 by 24 inches (610 by 610 mm)] [36 by 36 inches (914 by 914 mm)] [3 by 36 inches (76 by 914 mm)].
2. Rubber Floor Tile:
 - a. Class: [I-A, solid color] [I-B, through mottled].
 - b. Wearing Surface: [Smooth] [Textured].
 - c. Thickness: 1/8 inch (3.2 mm).
 - d. Size: 12 by 12 inches.
3. Molded-Rubber Floor Tile:
 - a. Class: [I-A, solid color] [I-B, through mottled].
 - b. Size: [18 by 18 inches (460 by 460 mm)] [19.7 by 19.7 inches (500 by 500 mm)] [24 by 24 inches (610 by 610 mm)] [39.4 by 39.4 inches (1000 by 1000 mm)].
 - c. Pattern: Raised [discs] [minidisks in square pattern] [minidisks in diamond pattern] [squares] [ribs].
4. Vinyl Composition Tile:
 - a. Class: [One, solid color] [Two, through pattern].
 - b. Wearing Surface: [Smooth] [Embossed].
 - c. Thickness: [3/32 inch (2.4 mm)] [0.100 inch (2.5 mm)] [1/8 inch (3.2 mm)].
 - d. Size: 12 by 12 inches.
5. Resilient Accessories:
 - a. Wall Base: [Rubber] [Vinyl].

- b. Stair Treads: [**Rubber**] [**Vinyl**].
- c. Risers.
- d. Stringers.
- e. Moldings: [**Rubber**] [**Vinyl**].

6. Metal edge strips.

C. RESILIENT TILE FLOORING SCHEDULE

- 1. **<Insert requirements for each type of resilient tile flooring.>**

END OF SECTION 09651